Textar Cera Tec

Anti-squeal lubricant



Clean bill of health

Brake Fluid • Brake Cleaner • Cera Tec

The non-metallic anti-squeal lubricant for braking systems is highly resistant (up to 1000°C).

The advantages of Cera Tec

- non-conductive
- contains no solid constituents
- suitable for anti-lock braking systems
- · facilitates brake installation
- reduces brake noise
- protects against scoring and corrosion
- free of copper + acids

Cera Tec is ideal for lubricating:

- disc and drum brakes
- compressors
- central lubricating systems
- axle bearings
- chains
- seat tracks
- sunroof guides
- battery contacts

Cera Tec is available in a 75 ml tube.

Article No.: 81000400

Minimum order quantity/unit: 36 tubes







Schlebuscher Str. 99 / 51381 Leverkusen / Germany T. +49 2171 703 0 / F. +49 2171 703 388 info@textar.com / www.textar.com





Textar Brake Fluid

DOT 3, DOT 4, DOT 4 PRO



Textar Brake Cleaner

Formula XT

The comprehensive range of Textar products includes three safety-optimized brake fluids that can be used individually:

- DOT 3 brake fluid is to be used for brake and clutch systems if specified in the car manufacturers guide lines.
- DOT 4 brake fluid is recommended for brake and clutch systems for which a nonpetroleum fluid is specified, including ABS.
- DOT 4 PRO low viscosity brake fluid is recommended for vehicles with ESP/ASR systems. Also suitable for all brake and clutch systems for which a non-petroleum fluid is specified.

Specifi- cation	Article No.	Boiling point	Wet boiling point	Information	Unit
DOT 3	95001200	~ 240° C	~ 149° C	SAE J 1703, ISO 4925 (Class 3), FMVSS 116 DOT 3	1 l bottle
DOT 4	95002100	~ 270° C	~ 163° C	SAE J 1704, ISO 4925 (Class 4), FMVSS 116 DOT 4	250 ml bottle
DOT 4	95002400	~ 270° C	~ 163° C	SAE J 1704, ISO 4925 (Class 4), FMVSS 116 DOT 4	500 ml bottle
DOT 4	95002200	~ 270° C	~ 163° C	SAE J 1704, ISO 4925 (Class 4), FMVSS 116 DOT 4	1 l bottle
DOT 4	95002300	~ 270° C	~ 163° C	SAE J 1704, ISO 4925 (Class 4), FMVSS 116 DOT 4	51 can
DOT 4 PRO	95006200	~ 266° C	~ 171° C	SAE J 1704, ISO 4925 (Class 6) FMVSS 116 DOT 4 (Viscosity at -40°C: 690 cSt Max.)	1 l bottle
DOT 4 PRO	95006300	~ 266° C	~ 171° C	SAE J 1704, ISO 4925 (Class 6), FMVSS 116 DOT 4 (Viscosity at -40°C: 690 cSt Max.)	5 I can

TEXTAR 4



Textar brake cleaner is a reliable way of removing oil, grease and dirt without leaving behind any residue.

Textar brake cleaner cleans all:

- brake, clutch and gear components
- starter motors and alternators
- carburetors, fuel pumps and engine components
- glass and metal surfaces before gluing

The advantages of Textar brake cleaner:

- does not destroy polystyrene
- does not contain any chlorinated solvents
- is listed with the German Federal Ministry for the Environment

How to use:

Spray a thick coating on the parts to be cleaned. Allow the solvent to drip and/or evaporate.

Repeat if necessary.

Textar brake cleaner is available in 500 ml spray cans.

Article No.: 96000100

Minimum order quantity: 72 cans Unit: 12 cans

